



DIN 20066 – P

BAUREIHE / SERIES: S = HEAVY

24° Dichtkegel mit O-Ring und Überwurfmutter nach ISO 8434-1

24° seal cone end with O-ring and union nut acc. ISO 8434-1

5

ZUBEHÖR • SCHLAUCHLEITUNGEN
ACCESSORIES • HOSE CONNECTIONS

QUALITÄT QUALITY	SCHLAUCH / HOSE					AVIT NG	ABMESSUNGEN [mm] DIMENSIONS			BESTELLCODE ORDER CODE
	DN	SIZE	WP	BP	BR		d	di	S2	
HQ	[mm]	[inch]	[bar]	[bar]	[mm]	[mm]				HQ DN TYP NG
2SN	6	¼"	420	1600	100	10	M18x1,5	3,9	19	2SN 6 AOS 10
	8	5/16"	350	1400	115	12	M20x1,5	5,4	22	2SN 8 AOS 12
	12	½"	275	1100	180	16	M24x1,5	9,5	30	2SN 12 AOS 16
	16	5/8"	250	1020	200	20	M30x2,0	12,6	36	2SN 16 AOS 20
	19	¾"	215	860	240	25	M36x2,0	14,8	46	2SN 19 AOS 25
	25	1"	165	660	300	30	M42x2,0	20	50	2SN 25 AOS 30
	31	1 ¼"	125	500	420	38	M52x2,0	26	60	2SN 31 AOS 38
4SP	38	1 ½"	90	360	500	50	M68x2,0	32	80	2SN 38 AOS 50
	12	½"	425	1900	175	16	M24x1,5	9,5	30	4SP 12 AOS 16
4SH	16	5/8"	420	1600	200	20	M30x2,0	12,6	36	4SP 16 AOS 20
	19	¾"	420	1750	210	25	M36x2,0	14,8	46	4SH 19 AOS 25
	25	1"	385	1750	220	30	M42x2,0	19,5	50	4SH 25 AOS 30
	31	1 ¼"	350	1400	420	38	M52x2,0	25	60	4SH 31 AOS 38
	38	1 ½"	300	1250	560	50	M68x2,0	30	80	4SH 38 AOS 50

WP Betriebsdruck | Working pressure

BP Berstdruck | Burst pressure

BR Biegeradius | Bend radius