



AVIT

- Geringer Strömungsverlust
 - Auch für Orbitalschweißverfahren lieferbar (-OF)
-
- Minimal flow loss
 - Also available for orbital welding system (-OF)

da	s	ABMESSUNGEN [mm] DIMENSIONS		GEWICHT WEIGHT	BESTELLCODE ORDER CODE
[mm]	[mm]	l	r	[kg]	TYP daxis
10	1,5	57	20	0,036	RB 10x1,5
	2,0			0,045	RB 10x2
12	2,0	65	30	0,056	RB 12x2
	3,0			0,075	RB 12x3
16	2,0	70	32	0,076	RB 16x2
	2,5			0,091	RB 16x2,5
20	2,0	88	45	0,137	RB 20x2
	2,5			0,166	RB 20x2,5
	3,0			0,194	RB 20x3
	4,0			0,243	RB 20x4
25	2,5	100	60	0,235	RB 25x2,5
	3,0			0,275	RB 25x3
	4,0			0,349	RB 25x4
	5,0			0,414	RB 25x5
30	3,0	140	75	0,436	RB 30x3
	4,0			0,558	RB 30x4
	5,0			0,669	RB 30x5
	6,0			0,768	RB 30x6
38	4,0	165	90	0,927	RB 38x4
	5,0			1,120	RB 38x5
	6,0			1,300	RB 38x6
	8,0			1,620	RB 38x8
50	5,0	235	195	3,250	RB 50x5
	6,0			3,840	RB 50x6
	8,0			4,800	RB 50x8
	10,0			5,800	RB 50x10

LIEFERVERARIANTEN
DELIVERY OPTIONS

Werkstoff / Material
Stahl, E 235+N (St 37.4) / Steel, E 235+N
Edelstahl 1.4571 / Stainless steel AISI 316Ti

BESTELLBEISPIEL
ORDER EXAMPLE

TYP daxis
RB 25x3
ERB 25x3

Bitte ergänzen Sie den Bestellcode für die gewünschte Liefervariante. | Please, complete the order code for the requested delivery option.